



Activo Mesa installation guide

Included:

- 1 x filter housing
- 1 x wrench
- 1 x cartridge
- 3 x adapters for faucet

STEP 1: INSTALLING THE CARTRIDGE

- Place the unit on a stable surface.
- Insert the included key and turn the collar of the unit counterclockwise. Lift the housing off the base of the unit.
- Unpack the new filter cartridge.
- Place the cartridge in the base of the unit.
- Put the housing back over the cartridge and onto the base, securing the collar with the key by tightening it clockwise.

STEP 2: INSTALLING THE FAUCET ADAPTER

The style of your faucet will determine which of the 3 included faucet adapters is required to install the diverter onto your faucet.

- The diverter should be mounted on your kitchen faucet. Remove the aerator/end piece from the faucet to determine if you have an internal, external, or no thread.

External Thread

- The clear gasket is pre-installed at the top of the diverter valve. Make sure it is properly positioned.
- Screw the diverter directly onto the end of the faucet.

Internal Thread

- Place the gasket inside the faucet adapter, if it is not already installed.
- Screw the faucet adapter into the internal threads of the faucet and tighten.
- Attach the diverter to the bottom of the faucet adapter.

No Thread

Use the larger universal adapter with the hose clamp.

- Slide the faucet adapter over the outside of your faucet as far as possible.
- Slide the hose clamp over the white rubber connection as high as possible.

- Tighten the clamp securely with a screwdriver.
- Attach the diverter to the bottom of the faucet adapter.

Make sure everything is tight, and let the water run slowly through the filter. If everything is sealed properly and there are no leaks, let the water run for 5 minutes to flush the cartridge before drinking the water.