



Activo Duo installation guide

Included in the set:

- 2 x filter housing
- 4 x fittings (pre-installed)
- 3 x hoses
- 2 x wrenches
- 2 x wall bracket
- 2 x filter cartridge

Inserting cartridges into the filter housings:

Insert the filter cartridges into the filter housings, then tighten the bottom and top together. Ensure that the cartridge is centered. If it is crooked, the top and bottom will be difficult to connect, and the cartridge will need to be adjusted. Use the included key to tighten fully.

Connecting the two filter housings:

The two filter housings are connected with the shortest of the three supplied hoses. Screw the hose onto each filter housing and tighten. Make sure the sequence is correct, where the pre-filter is filter housing number 1, and the carbon block cartridge is filter housing number 2. Also, ensure that the water flows correctly through the two filter housings. You can check this by looking at the top of each filter housing, where the markings "IN" and "OUT" are displayed. When the filter housings are assembled, the sequence should be IN-OUT-IN-OUT.

Installation:

Cold water outlet:

Turn off the water supply to the cold outlet, either at the main valve or, if available, at a small valve under the sink.

Locate your cold water outlet and disconnect your cold water hose.

Filter housings:

The filter housings can be mounted on the wall under the sink using the supplied wall brackets. If you choose to mount the filters, make sure to leave enough space below them to allow for future filter cartridge changes. The filter housings can also stand under the sink without being permanently mounted.

Attach the supplied hoses to each side of the filter housings. Pay attention to the arrows on the top of the filter housings indicating the direction of water flow. The two supplied hoses are not identical—one fits your cold water outlet, and the other is used to connect filter housing number 2 to the loose hose from your faucet.

Once both hoses are attached and tightened, you can connect the inlet hose to your cold water outlet. Then, attach hose 2 from filter housing number 2 to the loose hose from your faucet.

Carefully turn the water back on and check for any leaks. If leaks occur, you may need to tighten the connections where the leak is.

Let the water run for 5 minutes to flush out any excess carbon from the filter.